


780·24 QT

Ultra-narrow linewidth laser



Skylark supplies ultra-narrow linewidth QT series lasers to our partners in quantum sensing, quantum metrology, and other related technologies, at the specific wavelengths related to the atomic transitions they need to target. Our QT laser series includes the 780·24 QT for rubidium, as well as the 689·4 QT, 698·4 QT and 813·42 QT for strontium.

Key features



Ultra-narrow linewidth
 ≤ 0.3 MHz




High power stability
 $\leq 2.0\%$ over 8 hours



High spectral stability
 ± 1 pm over 8 hours



Excellent beam quality



Designed for strontium atoms

Applications

Quantum research — rubidium

Specifications	
Output beam parameters:	
Output power	up to 150 mW*
Wavelength	780·24 nm
Spectral bandwidth	≤ 0.3 MHz
Spatial mode	TEM ₀₀
Spectral stability	± 1.0 pm (over 8 hour operation)
Coherence length	> 100 m
Output power stability	$\leq 2.0\%$ (over 8 hour operation)
Output power noise	$\leq 0.1\%$ RMS (10 Hz – 10 MHz)
Beam divergence	≤ 1 mrad, diffraction limited
Beam diameter at output aperture	0.8 – 1.2 mm
Beam pointing stability	≤ 5 μ rad / °C
Polarisation ratio	$\geq 100:1$, vertical
Integration features:	
Plug-in USB connectivity	Combined heatsink
Versatile control software	Remote diagnostic support
Laser head dimensions:	
L x W	210 x 100 mm
Beam height	65 mm
Environmental conditions:	
Ambient temperature range	18 – 30 °C
Laser head interface stability	± 1.5 °C
Storage	0 – 50 °C
Humidity	5 – 95%, non-condensing
Optional accessories:	
Heatsink	Fan-Assisted
	Water-cooled with thermoelectric chiller
External power control module	0 – 100%, continuous
Tuning range, mode-hop free	25 – 50 GHz
Low power alignment beam mode	

* Other output powers available on request

Contact

✉ info@skylarklasers.com
☎ +44 (0) 131 333 2200
🌐 skylarklasers.com

Designed &
manufactured
in the UK



AVOID EYE OR SKIN EXPOSURE TO
DIRECT OR SCATTERED RADIATION
CLASS 4 LASER PRODUCT
MAX. POWER: 1000 mW
(IEC 60825-1)